

TIPO - TYPE		SERIE P300 - P300 SERIES									
L	giri/min RPM	10	25	50	100	150	200	250	300	400	500
Lungh. Rullo Roller lenght		C= Carico del rullo in daN - C= Roller loads in daN									
200/400	C	360	293	233	186	164	146	140	127	116	107
600		310	253	201	160	140	126	120	109	101	93
800		282	230	183	145	130	114	109	99	91	84
1000		263	215	169	136	120	108	101	93	85	79
1200		239	198	157	127	111	98	93	85	78	72
1400		220	179	141	113	100	90	85	78	71	65
1600		199	162	130	102	91	81	77	69	63	59
1800		178	144	115	91	81	72	67	62	57	53
2000		156	127	101	79	71	63	59	54	49	46
2200		134	112	87	68	61	52	50	48	42	40
2400		112	91	72	56	51	45	42	40	36	33
TIPO - TYPE		D	Velocità m/sec - Speed m/sec								
P3001	d 38	0,020	0,050	0,099	0,199	0,298	0,398	0,497	0,597	0,795	0,994
P3003	d 60	0,031	0,079	0,157	0,314	0,471	0,628	0,785	0,942	1,256	1,570
P3004	d 76	0,040	0,099	0,199	0,398	0,597	0,795	0,994	1,193	1,591	1,989
P3006	d 89	0,047	0,116	0,233	0,466	0,699	0,932	1,164	1,397	1,863	2,329
P3007	d 102	0,053	0,133	0,267	0,534	0,801	1,068	1,335	1,601	2,135	2,669

TIPO - TYPE		SERIE P400 - P400 SERIES									
L	giri/min RPM	10	25	50	100	150	200	250	300	400	500
Lungh. Rullo Roller lenght		C= Carico del rullo in daN - C= Roller loads in daN									
200/400	C	600	481	382	303	262	239	221	211	190	176
600		556	445	355	280	245	222	206	195	177	163
800		515	411	326	260	224	205	190	180	165	152
1000		475	390	301	239	207	189	175	165	151	140
1200		435	348	276	220	190	176	160	151	138	128
1400		392	315	249	199	171	156	145	136	125	116
1600		356	286	227	180	158	143	131	125	115	106
1800		327	263	208	165	144	132	121	116	106	97
2000		298	238	190	151	132	121	110	105	95	88
2200		268	215	173	139	120	110	99	94	86	80
2400		239	192	153	121	106	95	88	84	77	71
TIPO - TYPE		D	Velocità m/sec - Speed m/sec								
P4003	d 60	0,031	0,079	0,157	0,314	0,471	0,628	0,785	0,942	1,256	1,570
P4004	d 76	0,040	0,099	0,199	0,398	0,597	0,795	0,994	1,193	1,591	1,989
P4006	d 89	0,047	0,116	0,233	0,466	0,699	0,932	1,164	1,397	1,863	2,329
P4007	d 102	0,053	0,133	0,267	0,534	0,801	1,068	1,335	1,601	2,135	2,669
P4008	d 108	0,057	0,141	0,283	0,565	0,848	1,130	1,413	1,696	2,261	2,826
P4009	d 133	0,070	0,174	0,348	0,696	1,044	1,392	1,740	2,088	2,784	3,480

TIPO - TYPE		SERIE P500 - P500 SERIES									
L	giri/min RPM	10	25	50	100	150	200	250	300	400	500
Lungh. Rullo Roller lenght	C= Carico del rullo in daN - C= Roller loads in daN										
200/800	C	800	742	588	467	407	371	342	322	293	273
1000		743	690	546	435	378	345	318	300	274	254
1200		688	642	507	402	350	320	296	278	253	235
1400		632	588	466	369	322	294	271	256	233	216
1600		580	536	425	341	295	266	249	233	212	196
1800		522	483	385	306	266	241	223	210	192	177
2000		475	440	350	277	241	220	204	191	175	162
2200		423	393	311	245	215	198	180	169	155	145
2400		377	350	268	198	188	172	156	149	133	126
2600		320	301	232	173	161	150	135	131	115	109
TIPO - TYPE	D	Velocità m/sec - Speed m/sec									
P5006	d 89	0,047	0,116	0,233	0,466	0,699	0,932	1,164	1,397	1,863	2,329
P5007	d 102	0,053	0,133	0,267	0,534	0,801	1,068	1,335	1,601	2,135	2,669
P5008	d 108	0,057	0,141	0,283	0,565	0,848	1,130	1,413	1,696	2,261	2,826
P5009	d 133	0,070	0,174	0,348	0,696	1,044	1,392	1,740	2,088	2,784	3,480
P5010	d 159	0,083	0,208	0,416	0,832	1,248	1,664	2,080	2,496	3,328	4,161

TIPO - TYPE		SERIE P600 - P600 SERIES									
L	giri/min RPM	10	25	50	100	150	200	250	300	400	500
Lungh. Rullo Roller lenght	C= Carico del rullo in daN - C= Roller loads in daN										
200/1200	C	1000	932	817	649	566	517	479	450	410	378
1400		972	907	795	631	550	502	465	438	400	368
1600		920	858	752	598	519	475	440	412	377	349
1800		866	807	709	565	489	448	415	390	355	332
2000		813	757	665	530	460	419	375	365	333	311
2200		760	709	622	495	431	393	364	341	310	288
2400		707	660	582	458	401	365	345	318	286	267
2600		655	614	537	422	369	336	315	295	265	246
TIPO - TYPE	D	Velocità m/sec - Speed m/sec									
P6006	d 89	0,047	0,116	0,233	0,466	0,699	0,932	1,164	1,397	1,863	2,329
P6007	d 102	0,053	0,133	0,267	0,534	0,801	1,068	1,335	1,601	2,135	2,669
P6008	d 108	0,057	0,141	0,283	0,565	0,848	1,130	1,413	1,696	2,261	2,826
P6009	d 133	0,070	0,174	0,348	0,696	1,044	1,392	1,740	2,088	2,784	3,480
P6010	d 159	0,083	0,208	0,416	0,832	1,248	1,664	2,080	2,496	3,328	4,161